DATE: 14.01.2016



Below is an update to the schedule of standard cylinder lengths for Optima door systems. This was previously issued in June 2013.

Door Family	Door Type	SG	DG	Frame Type	Lock	Key Side Dimension	Turn Side Dimension
AXILE	Clarity	✓	×	Microflush	Infinity Patch Lock	30mm	30mm
AXILE	Pulse	✓	×	Frameless	Infinity Patch Lock	30mm	30mm
AXILE	Flush-Bond	×	√	Microflush	WSS Dead & Sash Locks	35mm	35mm
AXILE	Conceal	×	✓	Frameless	Optima Patch Lock	65mm	35mm
AXILE	Harmony	×	✓	Frameless	Optima Patch Lock	65mm	35mm
EDGE	Symmetry	✓	✓	Microflush	Britton Sash Lock	40mm	30mm
EDGE	Symmetry	✓	✓	Microflush	EuroSpec Dead Lock	40mm	30mm
EDGE	Affinity	✓	✓	Microflush	Britton Sash Lock	40mm	30mm
EDGE	Affinity	✓	✓	Microflush	EuroSpec Dead Lock	40mm	30mm
ELITE	Affinity	×	✓	Microflush	Nemef Dead & Sash Locks	40mm	75mm
ELITE	Aero	✓	*	~	OMEC Hook Lock	30mm	30mm
KINETIC	Seal	✓	*	~	Minima Hook Lock	30mm	30mm
KINETIC	Aero	✓	*	~	OMEC Hook Lock	30mm	30mm
KINETIC	Align	✓	×	~	OMEC Hook Lock	50mm	30mm
TECHNISHIELD	Integrity	✓	*	Microflush	Infinity Patch Lock	30mm	30mm
TIMBER	44mm	×	×	Microflush	Britton Dead & Sash Locks	30mm	30mm
TIMBER	54mm	×	×	Microflush	Britton Dead & Sash Locks	40mm	30mm

Please address any queries to Peter Long at: peter.long@optima-group.co.uk

Cylinder Dimensions for Standard Optima Door Systems Title: 000504

Ref: